

What is MoGo Dapter™?

Now you can add Bluetooth wireless capabilities to your USB tablet or notebook computer. MoGo Dapter™ is a technologically advanced wonder, featuring patent-pending mechanics, an ultra low-profile design.

MoGo Dapter™ uses advanced technologies - Bluetooth v2.0 + EDR and USB 2.0 - to provide you with quicker connection times, enhanced voice and multimedia quality, greater Wi-Fi environments, and up to three-times-faster data-transfer speeds than v1.2.



Who's MoGo Dapter™ meant for?

MoGo Dapter™ is specifically designed for road warriors who do not have embedded Bluetooth functionality on their laptops and hate carrying around full-sized bulky adapters, that are quite often left at home. MoGo Dapter™ provides business travelers with a solution to their problem, making it easier for them to work on the road.

What's so special about MoGo Dapter™?

MoGo Dapter™ makes quantum leaps over other Bluetooth adapters when it comes to mobility and usability. Its design lets business travelers use MoGo Dapter™ in virtually any environment. MoGo Dapter™ Ultra low-profile, only .4", supports "plug it and forget it" for the ultimate in portability. Once you install MoGo Dapter™ into your USB connector you do not need to unplug the unit during travel, as its mechanical design does not protrude.

Features

- Ultra low-profile design allows "plug it and forget it" for mobile user.
- Bluetooth 2.0 EDR supports higher transfer than v1.2



Plug it



Go



Specifications

| | |
|------------------------------|---|
| General | <ul style="list-style-type: none">• Supports up to 7 slave devices |
| Standards | <ul style="list-style-type: none">• Bluetooth 2.0 EDR |
| Transfer Rates (Max) | <ul style="list-style-type: none">• 3.0Mbps Asymmetrical |
| RF-Wireless Frequency | <ul style="list-style-type: none">• 2400 - 2483.5 MHz for USA/Europe/Japan |
| Antenna | <ul style="list-style-type: none">• 2dBi On-Board• Integrated Chip |
| Receiver Sensitivity | -80 dBm typical across passband under high interference environments |
| Range | Up to 30 feet (peer-to-peer) |
| RF Technology | Frequency Hopping Spread Spectrum |
| System Requirements | <p>For Windows Computers</p> <ul style="list-style-type: none">• Windows XP/2000/Me/98se with USB Support• One Available USB Port• CD-ROM Drive <p>For Macintosh Computers</p> <ul style="list-style-type: none">• Macintosh OS X v10.2 with USB Support• One Available USB Port |
| Operating Voltage | 5VDC +/- 10% |
| Power Consumption | <ul style="list-style-type: none">• Max 33mA in transmit mode• Max 38mA in receive mode• Max 259uA in sleep mode |
| Dimensions | <ul style="list-style-type: none">• L = 0.4 in.• W = .73 in.• H = 0.37 in. |
| Weight | 0.09 oz (39g) |



©2007 Newton Peripherals, LLC. All Rights Reserved. Bluetooth is a registered trademark of Bluetooth SIG. All other trademarks and registered trademarks are the property of their respective holders. Patents Pending.